



# NU050 / NU075



## Features

- Easy to use timer
- Electrical, gas and steam heating
- Large door opening for easy loading and unloading (ø68cm)
- Galvanized drum
- Radial airflow
- Large lint filter

## Options

- Stainless steel drum
- Stainless steel front panel
- Coin operated version
- Reversing drum
- Residual moisture control:
  - Lower energy and utility costs
  - Lower linen replacement costs
- Fire suppression system



# Dimensions & Specifications

Type		NU050	N075
<b>CAPACITY</b>			
Capacity	kg	25	34
Drum Volume	l	528	634
Drum Diameter	mm	Ø939	Ø939
<b>AIRFLOW</b>			
50 Hz	l/s	354	354
60 Hz	l/s	354	434
<b>DRYING AVERAGE</b>			
Gas Heating	g/min	453	616
Electric Heating	g/min	399	381
<b>MOTOR</b>			
Fan	kW	0,375	0,559
Drive	kW	0,375	0,559
<b>GAS HEATING</b>			
Energy	kW	38,1	48,3
	kBTU/h	130	165
Electrical Connection		1x200-240V 50/60Hz, 3x200-240V 50/60Hz 3x380-415V 50Hz, 3x380-415/440V 60Hz	
Gas Connection	NPT	1/2"	1/2"
<b>STEAM HEATING</b>			
High Pressure 6,9 bar	kW	52	61,6
	kBTU/h	178	210,3
Electrical Connection		1x200-240V 50/60Hz, 3x200-240V 50/60Hz 3x380-415V 50Hz, 3x380-415/440V 60Hz	
Steam Connection	NPT	3/4"	3/4"
<b>ELECTRICAL HEATING</b>			
Energy	kW	30	30
Electrical Connection		3x200-240V 50/60Hz, 3x380-415 50Hz, 3x380-415/440V 60Hz	
EXHAUST	ø/mm	203	203
<b>DIMENSIONS</b>			
HxWxD	mm	1946x981x1226	1946x981x1378
Net Weight	kg	247	279
<b>TRANSPORT DATA</b>			
Gross Weight	kg	273	307
Packing HxWxD	mm	2057x1054x1323	2057x1054x1433

Side NU050 075

Back NU050 075 Electric

Back NU050 075 Gas

Back NU050 075 Steam

