



SAPPHIRE
COMMERCIAL LAUNDRY EQUIPMENT

Sales - Rentals - Parts
info@sapphirelaundry.co.uk
www.sapphirelaundry.co.uk



PB3215 / PB3221

GIRBAU
INNOVATIVE LAUNDRY SOLUTIONS



Features



Autospeed

The Autospeed system automatically adjusts the ironing speed depending on the type of linen and the degree of dampness. With Autospeed an even temperature is rapidly achieved. The result: even ironing. The new sensor assembly provides more accuracy, reliability and durability.



Logic Control

Easy to use Logic Control system, with an LCD screen.



Ergonomics

The position and width of the feeding table where the linen is positioned, and good foot access under the table make for effortless ironing operations. The operator can maintain a comfortable and natural position while, thereby avoiding unnecessary stress.

Quality

Girbau's exclusive kinematic strap tensioning system maintains uniform ironing cylinder pressure, resulting in an excellent finish.

Reliability

Twenty year's experience in the industry, with thousands of flatwork ironers operating in businesses around the world, provides clear proof of the reliability of Girbau ironers.

T: 0121 663 0500

E: info.sapphirelaundry.co.uk

W: www.sapphirelaundry.co.uk

Unit 13, Warwick House Industrial Park, Banbury Road, Southam, Warwickshire, CV47 2PT

Dimensions & Specifications

Model			PB3215	PB3221		
Traction	Max. motor power (50Hz)		kW	0,55		
	Power of high speed motor (50Hz)		kW	0,67		
Heating	Electric	Electric heating power	kW	15,1	21,2	
		Evaporation	l/h	15,0	20,0	
	Gas	Gas power Atmospheric Burner	kW (Hi)	19,9	27,7	
		Evaporation	l/h	15,0	20,0	
		Gas power Premix Burner	kW (Hi)	-	-	
	Steam	Evaporation	l/h	-	-	
		Steam power	kW	-	-	
	Options	Folder		-		
Double photocell assembly		-				
High speed option		Yes	Yes			
Dimensions and weights	Cylinder diameter		mm (in.)	325 (12,8)		
	Useful length of cylinder		mm (in.)	1.540 (60,6)	2.120 (83,5)	
	Speed		m/mm (ft/min)	1-5 (3-16)		
	High speed option		m/mm (ft/min)	1-11 (3-36)		
	Noise level		dB (A)	< 70		
	Net weight G-E	PB kg (lbs)		459 (1.012)	561 (1.237)	
		PBP kg (lbs)		-		
	Net weight V	PB kg (lbs)		-		
		PBP kg (lbs)		-		
	Gross weight G-E	PB kg (lbs)		617 (1.360)	740 (1.630)	
		PBP kg (lbs)		-		
	Gross weight V	PB kg (lbs)		-		
		PBP kg (lbs)		-		
	Height H		mm (in.)	1.416 (55,7)		
	Width L		mm (in.)	2.313 (91,1)	2.895 (114)	
Depth P		mm (in.)	872 (34,3)			

* Hi - lower heating value

GIRBAU S.A. reserves the right to change design and/or specification without notice

