



# DX13/DX16/DX24

primus

## Features

- Controls:
  - Dual Digital Control or OPL Micro
  - Coin operated version: XQ-Control
- Electrical or Gas heating
- Large door opening for easy loading and unloading (57cm, DX13,16,Ø68cm DX24)
- Galvanized drum
- Axial airflow
- Large lint filter

## Options

- Stainless steel drum
- Stainless steel front panel with black painted door
- Coin operated version
- Reversing drum
- Residual moisture control Sensodry+® (only with Full OPL Micro)
  - lower energy and utility costs
  - lower linen replacement costs
- SafeTech™ Fire Suppression System



FAST DRYING



EASY  
OPERATION



SERVICE  
FRIENDLY



## Dimensions & Specifications

Type		DX13	DX16	DX24
<b>CAPACITY</b>				
Capacity	kg	13	16	24
Drum Volume	l	270	350	490
Drum Diameter	mm	Ø 673	Ø 762	Ø 838
<b>AIRFLOW</b>				
Airflow	l/s	240	280	330
<b>DRYING AVERAGE</b>				
Gas Heating	g/min	267	349	485
Electric Heating	g/min	258	340	371
<b>MOTOR</b>				
Fan	kW	0,4	0,4	0,4
Drive	kW	0,2	0,2	0,4
<b>GAS HEATING</b>				
Energy	kW	21,4	26,4	32,8
Energy	kBTU/h	73	90	112
<b>Electrical Connection</b>		1x100-120V/50-60Hz, 1-3x200-240V/50-60Hz 3x440-480V/50-60Hz, 3x380-415V/50-60Hz		
<b>Gas Connection</b>	NPT	1/2"	1/2"	1/2"
<b>ELECTRICAL HEATING</b>				
Energy	kW	21	24	27
<b>Electrical Connection</b>		1x200-208V/50-60Hz, 3x200-208V/50-60Hz, 1x230-240V/50-60Hz 3x230-240V/50-60Hz, 3x380V/50-60Hz, 3x400-415V/50-60Hz 3x440V/50-60Hz, 3x460-480V/50-60Hz		
<b>EXHAUST</b>	Ø /mm	150	200	200
<b>DIMENSIONS</b>				
Size HxWxD	mm	1625x710x1155	1625x800x1155	1700x900x1350
Net Weight (E)	kg	150	160	200
Net Weight (G,S)	kg	145	155	195
<b>TRANSPORT DATAT</b>				
Packed (foil) HxWxD	mm	1270x760x1240	1720x840x1240	1790x900x1450
Gross Weight (foil, E)	kg	160	170	220
Gross Weight (foil, G, S)	kg	155	165	215
Packed (crate) HxWxD	mm	2210x880x1320	2210x950x1320	2210x1020x1520
Gross Weight (crate, E)	kg	220	230	300
Gross Weight (crate, G, S)	kg	214	220	295

