

SPC10 / SDC10



Features - Washer Extractor

- Stainless steel outer and inner drum
- Industry-leading 440 G-Force extraction removes more moisture, minimising drying times and utility
- Totally freestanding: can be installed on any floor and any level
- Suspension with new out-of-balance logic
- Soap box with four compartments
- Door opens 180° for easy loading and unloading
- Coin boxes and coin mechanisms available as an option
- Standard with drain pump, drain valve optionally available
- Top, front and side panels standard available in anthracite grey
- Electrical heating or boiler-fed
- 6 wash programs
- Possibility of programming cycle modifier options >> Added prewash >> Extra wash time >> Extra rinse
- LED indication of the status of the program
- Time remaining countdown



Features - Dryer

- Galvanized steel cylinder
- Oversized lint filter located in front for easy cleaning
- Powerful exhaust blower assures short drying times and low operating costs
- Wide door opening of 180° for easy loading and unloading
- Coin boxes and coin mechanisms
- Top, front and side panels standard available in anthracite grey
- Electrical or gas heating
- 4 drying programs
- LED indication of the status of the program
- Time remaining countdown









Dimensions & Specifications

_		
Туре		SP10
CAPACITY	kg	10
DRUM VOLUME	I	96,8
MOTOR	kW	0,67
Frequency Controlled	KVV	
EXTRACTION SPEED	rpm	1200
G-FACTOR		440
ELECTRICAL CONNECTION		1x220-240V 50Hz
		1x220-240V 60Hz
		3x220-240V 50Hz
		3x380-415V+N 50Hz
ELECTRICAL HEATING	kW	4,8
DRAIN		
Pump		Standard
Drain Valve		Available
DIMENSIONS		
HxWxD	mm	1126x683x704
Net Weight	kg	119
TRANSPORT DATA		
Volume (packed)	m3	0,77
Packed HxWxD	mm	1150x760x860
Gross Weight	kg	128

Туре		SP10
CAPACITY	kg	10
DRUM VOLUME	I	198
ELECTRICAL CONNECTION		1x220-240V 50Hz
		3x380-415V+N 50Hz
ELECTRICAL HEATING	kW	5,3 (400V)
GAS HEATING	kW	7,3
MOTOR POWER		0,25
DIMENSIONS		
HxWxD	mm	1126x683x711
Net Weight	kg	74
TRANSPORT DATA		
Volume (packed)	m3	0,71
Packed HxWxD	mm	1150x760x860
Gross Weight	kg	79

^{*} To combine with the collector it's required a base frame (200mm height) is ordered















