



WLS 20



Features

- Standard stainless steel drum with large diameter
- Easy control - Easy to use microprocessor
- Combination of Radial and Axial airflow
 - Maximal heat transfer
 - Low energy consumption
 - Short drying time
- Large door opening for easy loading and unloading

Options

- Coin operated version
- Reversing drum
- Professional control - Full control
- Residual moisture control:
 - safe drying of delicate linen
 - humidity detection in %
 - ideal for dry cleaners, fire depts
 - available on Easy and Professional control



Dimensions & Specifications

Type		NU050
CAPACITY		
Capacity	kg/lb	9/20
Drum Volume	l	190
Drum Diameter	mm	Ø760
Number of Drums		1
Number of Loading Doors		1
AIRFLOW		
DRYING AVERAGE		0,150
MOTOR		
Fan	kW	0.75
Drive	kW	0,18
GAS HEATING		
Gas Connection	inch	3/4"
Electrical Connection		3x380-415V 50/60Hz, 3x220-240V 50Hz 3x208-240V 60Hz, 3x440V 60Hz
Energy	kW	12,5
	kBTU/h	42,7
ELECTRICAL HEATING		
Electrical Connection		3x200-240V 50/60Hz, 3x380-415 50Hz, 3x380-415/440V 60Hz 3x208-240V 60Hz, 3x440V 60Hz, 3x480V 60Hz
Energy	kW	9/12
PROGRAMMER		
Easy Control – Antivandal (ECT)		Standard
Professional Control (FCT)		Available
EXHAUST		
DIMENSIONS		Ø150
HxWxD	mm	1465x795x815
TRANSPORT DATA		
Gross Weight	kg	180
Net Weight	kg	170
Packing HxWxD	mm	1570x880x885

The data concerning dimensions of machines include all extended parts

